



BS10R
bluetooth ring
scanner

FEATURES

Scan hands-free.

The BS10R is capable of reading a wide range of 1D and 2D barcodes with outstanding performance. The ring scanner was designed to fit comfortably on your hand without getting in the way of daily tasks, like carrying boxes. Its trigger button is positioned to be easy to operate with one hand and a built-in buzzer and LED gives instant feedback on each scan.

Convenient communication.

With the click of a button, the BS10R pairs to your preferred device via Bluetooth 4.1 wireless technology. Whether your system runs on Windows, Android or iOS and whether you use a tablet, a smartphone, a computer or another Newland device, connecting the ring scanner is always easy. It provides freedom of movement up to 30 meters from the host and can be used in USB HID Keyboard and SPP connection modes.

Large storage capacity.

Not all operations require instant feedback from a connected device, or allow you to carry such a device with you. For those situations, the BS10R is equipped with 16GB of storage, which holds the data of up to 50k barcodes until you are able to move it to your system of choice.

Full-shift battery life.

The BS10R battery comfortably lasts a minimum of 8 hours, even when your operations require a constant Bluetooth connection and intensive scanning. In standby mode, the device will last an impressive 30 days.

Small but strong.

Built to withstand 1.5 meter drops to concrete and bumps on metal surfaces, the BS10R is reliable, even in rough operational environments.

Application Scenarios

Warehouse management • inventORIZATION • logistics.

BS10R

bluetooth ring scanner

newland-id.com

Performance	Image Sensor	640x480 CMOS	
	Illumination	White LED	
	Aimer	Red LED (650 nm±10 nm)	
	Symbolologies	2D	PDF417, Data Matrix (ECC200,ECC000,050,080 100, 140), QR Code.
		1D	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey
	Decoding chip	ARM Cortex 32 bits	
	Resolution	≥5mil	
	Storage	16MB	
	Bluetooth module	Bluetooth 4.1	
	Indicator	LED light, Buzzer, Vibration (Optional)	
	Charging voltage/current	5V/1A	
	Time of endurance	Continuously work 8 hours under normal temperature (5 second/scan)	
	Charging Time	<2 hours	
	Standby time	>30 days	
	Environmental	Operating Temperature	0°C to 40°C
Storage Temperature		-40°C to 60°C	
Humidity		5% to 95% relative humidity (no condensation)	
Drop		Resist about 6 times drops from 1.5m to concrete	
Ambient light immunity		Under normal office and factory ambient lighting conditions, or exposed to the sun won't take any effect to it.	
Electrostatic discharge		In line with 15KV air discharge and 8KV contact discharge requirements	

Specifications are subject to change without notice.

Version: V1.0

Newland EMEA HQ

+31 (0) 345 87 00 33
info@newland-id.com
newland-id.com

D-A-C-H

+49 (6) 182 82916-16
info@newland-id.de

United Kingdom

+44 (0) 7771 631387
info@newland-id.co.uk

France

+39 (0) 345 8804096
france@newland-id.com

Russia

+31 (0) 345 87 00 33
russia@newland-id.com

Benelux

+31 (0) 345 87 00 33
benelux@newland-id.com

Turkey

+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica

+31 (0) 345 87 00 33
info@newland-id.com

Middle East

+39 (0) 345 8804096
middleeast@newland-id.com

Italy

+39 (0) 342 0562227
italy@newland-id.com

South Africa

Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic

+46 (0) 70 88 47 767
nordic@newland-id.com

Iran

+90 (0) 544 538 40 49
iran@newland-id.com